

VIA FACSIMILE TRANSMISSION 571-273-8300

PATENT  
Attorney Docket: 135248 (AT 12553-1035)

## IN THE CLAIMS

1. (Currently Amended) A method for acquiring ultrasound data, comprising:

transmitting ultrasound signals from a transducer into an area of interest;

receiving, at the transducer, ~~acquiring~~ ultrasound echo signals from an ~~the~~ area of interest;

converting ~~analyzing~~ said ultrasound echo signals received at the transducer into produce  
a first data stream associated with a first receive beam; and

decimating said first data stream by passing at least two consecutive data samples and by removing at least two other consecutive data samples therefrom to form a first decimated data stream.

2. (Original) The method of claim 1, further comprising:

analyzing said echo signals to produce a second data stream associated with a second receive beam that is spatially different from said first receive beam; and

multiplexing said first and second data streams together.

3. (Original) The method of claim 1, further comprising:

analyzing said echo signals to produce a second data stream associated with a second receive beam that is spatially different from said first receive beam; and

decimating said second data stream by passing at least two consecutive data samples and by removing at least two other data samples therefrom to form a second decimated data stream.

4. (Original) The method of claim 1, further comprising:

VIA FACSIMILE TRANSMISSION 571-273-8300

PATENT  
Attorney Docket: 135248 (AT 12553-1035)

analyzing said echo signals to produce a second data stream associated with a second receive beam that is spatially different from said first receive beam; and

decimating said second data stream to pass at least two consecutive data samples that align in time with said two other data samples removed from said first data stream.

*Previously Presented*  
5. (~~Currently Amended~~) The method of claim 1, further comprising acquiring said echo signals simultaneously from multiple different receive beams and repeating said analyzing and decimating steps for multiple data streams associated with said multiple different receive beams.

6. (Currently Amended) An ultrasound system, comprising:

a transmitter for transmitting ultrasound signals into an area of interest;

a receiver for receiving ultrasound echo signals from the area of interest from transmitted ultrasound signals;

a beamformer processing said echo signals to simultaneously form first and second data streams associated with different first and second receive beams;

a decimator for passing consecutive data samples from at least one of said first and second data stream and for removing consecutive data samples from said first and second data streams, said decimator removing a different number of consecutive said data samples based on a band-pass mode; and

a multiplexor for combining said first and second data streams such that data samples passed in said first data streams are intermixed with data samples passed in said second data stream to form a multiplexed data stream.

7. (Cancelled)

VIA FACSIMILE TRANSMISSION 571-273-8300

PATENT  
Attorney Docket: 135248 (AT 12553-1035)

8. (Original) The ultrasound system of claim 6, further comprising at least two processors receiving and dividing said echo signals from said receiver into said first and second data streams, said first and second receive beams differing spatially with respect to said receiver.

9. (Original) The ultrasound system of claim 6, further comprising an anti-aliasing filter passing data based on said band-pass mode, said band-pass mode being one of low-band, mid-band, and high-band.

10. (Original) The ultrasound system of claim 6, further comprising a system controller identifying said band-pass mode.

11. (Original) The ultrasound system of claim 6, further comprising said band-pass mode being one of low-band, mid-band, and high-band, said at least one decimator removing two consecutive said data samples when said band-pass mode is said mid-band, said at least one decimator removing every other said data sample when said band-pass mode is said high-band.

12. (Currently Amended) A demodulator for use with an ultrasound system to demodulating ultrasound data streams, the ultrasound system having a transmitter for transmitting ultrasound signals into an area of interest, a receiver for receiving ultrasound echo signals from the area of interest from transmitted ultrasound signals. a beamformer for processing said echo signals to form a data stream. the demodulator comprising:

an input receiving ~~at~~ the data stream, said data stream comprising mid-band data;

a multiplier interleaving said data stream with a time dependent signal; and

a filter filtering said data stream, said filter further comprising coefficients having two consecutive data samples representative of a desired impulse response interleaved with two consecutive data samples being zeros, said filter outputting a filtered data stream.

13. (Original) The demodulator of claim 12, said data stream further comprising data pairs, said filter further comprising coefficients interleaved with zeros.

VIA FACSIMILE TRANSMISSION 571-273-8300

PATENT  
Attorney Docket: 135248 (AT 12553-1035)

14. (Original) The demodulator of claim 12, said filter filtering said data stream with a coefficient set that is different for odd and even numbered time index.

15. (Previously Presented) The demodulator of claim 12, said data stream further comprising multiplexed mid-band data, said multiplexed mid-band data being interleaved every two consecutive data samples.

16. (Original) The demodulator of claim 12, said data stream having a first frequency, said filter outputting said filtered data stream at a sampling rate being one of equal to said first frequency and two times said first frequency.

17. (Currently Amended) A method for acquiring ultrasound data, comprising:

transmitting ultrasound signals from a transducer into an area of interest;

receiving, at the transducer, ultrasound echo signals from the area of interest;

acquiring echo signals from an area of interest;

converting said ultrasound echo signals into producing first and second data streams  
associated with first and second receive beams based on said echo signals, said first and second data streams having a total bandwidth;

filtering said first and second data streams to form first and second filtered data streams, said first and second filtered data streams having a bandwidth comprising one of a low-band, mid-band, and high-band, said low-band, mid-band, and high-band bands being based on said total bandwidth; and

decimating said first and second filtered data streams to form first and second decimated data streams; and

multiplexing said first and second decimated data streams to form a multiplexed data stream.

VIA FACSIMILE TRANSMISSION 571-273-8300

PATENT  
Attorney Docket: 135248 (AT 12553-1035)

18. (Cancelled)

19. (Original) The method of claim 17, said first and second decimated data streams having a bandwidth of one-quarters to three-quarters of said total bandwidth.

20. (Original) The method of claim 17, said filtering step applying coefficients based on said bandwidth, said coefficients being different for each of said low-band, mid-band, and high-band bands.